

GRAINMASTER® SILOS

45° Cone Base — Urea Fertiliser Storage

	MODEL	CAPACITY (m³)	TONNES*	DIAMETER (m)	OVERALL HEIGHT (m)	AUGER LGTH REQ'D (ft) **
1500 SERIES	1501	38	29.15	4.6	5.11	30
	1501.5	47.4	36.36	4.6	5.68	33
	1502	56.8	43.57	4.6	6.25	36
	1502.5	66.2	50.78	4.6	6.82	40
	1503	75.5	57.91	4.6	7.39	43
	1503.5	84.9	65.12	4.6	7.96	46
	1504	94.3	72.33	4.6	8.53	49
	1504.5	103.7	79.54	4.6	9.1	53
	1505	113.1	86.75	4.6	9.67	56
1800 SERIES	1801	60.4	46.33	5.5	5.84	34
	1801.5	73.9	56.68	5.5	6.41	37
	1802	87.4	67.04	5.5	6.98	40
	1802.5	100.7	77.24	5.5	7.55	44
	1803	114.5	87.82	5.5	8.12	47
	1803.5	128	98.18	5.5	8.69	50
	1804	141.5	108.53	5.5	9.26	53
	1804.5	155	118.89	5.5	9.83	57
	1805	168.5	129.24	5.5	10.4	60
	1805.5	182.0333	139.62	5.5	10.97	64
	1806	195.6	150.03	5.5	11.53	66
	1806.5	208.9	160.23	5.5	12.1	70

* Tonnes based on Granulated Urea density of 767kg/m³

** Length of auger based on a lift angle of 35 degrees

FERTILISER SILOS have 304 stainless steel roof and wall sheets, and Valspar 2 Pac Polyester Urethane paint applied at 100 Microns DFT to cone bases and support legs. They come included with top in fill hatch, roof door, full height caged external ladders complete with platform, cone access door, outer slide gate assembly, and are weatherproofed.

Grainmaster Silos has been manufacturing a variety of different storage solutions, servicing a number of industries worldwide, collectively for over 125 years.

Grainmaster Silos incorporate a large range of conical-based silos in capacities from 5 tonnes through to 300 tonnes for both on-farm and commercial applications.

There are also flat-bottom silos available with capacities up to 6000 tonnes.

The complete Grainmaster product range can be manufactured from mild steel, galvanized sheet and coil, stainless steel, aluminium or colorbond, to

ensure the best results for the product being stored.



CONTACT US AT

57-75 Industrial Avenue, Toowoomba, QLD 4350 EMAIL: Steveb@thedaveygroup.com.au PHONE: (07) 46347767