

GRAINMASTER® SILOS

1500 Series Silos

	MODEL	CAPACITY (m3)	TONNES *	DIAM (m)	OVERALL HEIGHT (m)	AUGER LGTH (ft) **
30° CONE BASE SILO	1501	33.2	27.66	4.6	4.26	25
	1501.5	42.5	35.40	4.6	4.83	28
	1502	51.9	43.23	4.6	5.4	31
	1502.5	61.3	51.06	4.6	5.97	35
	1503	70.7	58.89	4.6	6.54	38
	1503.5	80.1	66.72	4.6	7.11	41
	1504	89.5	74.55	4.6	7.68	44
	1504.5	98.8	82.30	4.6	8.25	48
	1505	108.2	90.13	4.6	8.82	51
	1505.5	117.6	97.96	4.6	9.39	54
	1506	127	105.79	4.6	9.96	57
	1506.5	136.4	113.62	4.6	10.53	61
	1507	145.8	121.45	4.6	11.1	64
35° CONE BASE SILO	1501	34	28.78	4.6	4.51	26
	1501.5	43.9	36.15	4.6	5.07	30
	1502	53.3	43.53	4.6	5.64	33
	1502.5	62.7	50.90	4.6	6.21	36
	1503	72.1	58.27	4.6	6.78	39
	1503.5	81.5	65.65	4.6	7.35	43
	1504	90.7	73.02	4.6	7.92	46
	1504.5	100.3	80.39	4.6	8.49	49
	1505	109.6	87.76	4.6	9.06	52
	1505.5	119	95.14	4.6	9.63	56
	1506	128.7	102.51	4.6	10.2	59
	1506.5	137.8	109.88	4.6	10.77	62
	1507	147.2	117.26	4.6	11.34	66

*Tonnes based on wheat density of 833kg/m³ ** Length of auger based on a lift angle of 35 degrees

Grainmaster Silos has been manufacturing a variety of different storage solutions, servicing a number of industries world-wide, collectively for over 125 years.

Grainmaster Silos incorporate a large range of conical-based silos in capacities from 5 tonnes through to 300 tonnes for both on-farm and commercial applications. There are also flat-bottom silos available with capacities up to 6000 tonnes.

The complete Grainmaster product range can be manufactured from mild steel, galvanized sheet and coil, stainless steel, aluminium or colorbond, to ensure the best results for the product being stored.



CONTACT US AT

57-75 Industrial Avenue, Toowoomba, QLD 4350 EMAIL: Steveb@thedaveygroup.com.au PHONE: (07) 46347767

GRAINMASTER® SILOS

1500 Series Silos

	MODEL	CAPACITY (m3)	TONNES *	DIAM (m)	OVERALL HEIGHT (m)	AUGER LGTH (ft) **
45° CONE BASE SILO	1501	38	31.65	4.6	5.11	30
	1501.5	47.4	39.48	4.6	5.68	33
	1502	56.8	47.31	4.6	6.25	36
	1502.5	66.2	55.14	4.6	6.82	40
	1503	75.5	62.89	4.6	7.39	43
	1503.5	84.9	70.72	4.6	7.96	46
	1504	94.3	78.55	4.6	8.53	49
	1504.5	103.7	86.38	4.6	9.1	53
	1505	113.1	94.21	4.6	9.67	56
	1505.5	122.5	102.04	4.6	10.24	59
	1506	131.9	109.87	4.6	10.81	62
	1506.5	141.2	117.62	4.6	11.38	66
	1507	150.6	125.45	4.6	11.95	69
60° CONE BASE SILO	1501	46.3	38.57	4.6	6.6	38
	1501.5	55.8	46.48	4.6	7.17	42
	1502	65.1	54.23	4.6	7.74	45
	1502.5	74.5	62.06	4.6	8.31	48
	1503	83.9	69.89	4.6	8.88	51
	1503.5	93.3	77.72	4.6	9.45	55
	1504	102.7	85.55	4.6	10.02	58
	1504.5	112	93.30	4.6	10.59	61
	1505	121.5	101.21	4.6	11.16	64
	1505.5	130.8	108.96	4.6	11.73	68
	1506	140.2	116.79	4.6	12.3	71
	1506.5	149.6	124.62	4.6	12.87	74
	1507	159	132.45	4.6	13.44	77

*Tonnes based on wheat density of 833kg/m³ ** Length of auger based on a lift angle of 35 degrees

Grainmaster Silos has been manufacturing a variety of different storage solutions, servicing a number of industries world-wide, collectively for over 125 years.

Grainmaster Silos incorporate a large range of conical-based silos in capacities from 5 tonnes through to 300 tonnes for both on-farm and commercial applications. There are also flat-bottom silos available with capacities up to 6000 tonnes.

The complete Grainmaster product range can be manufactured from mild steel, galvanized sheet and coil, stainless steel, aluminium or colorbond, to ensure the best results for the product being stored.



CONTACT US AT

57-75 Industrial Avenue, Toowoomba, QLD 4350 EMAIL: Steveb@thedaveygroup.com.au PHONE: (07) 46347767